

II. CLAIM AMENDMENTS

1. (Currently Amended) A mobile communication terminal comprising:

a processor unit being configured to control said communication terminal,

an electronic memory having at least one music data sequence stored thereon~~received therein~~, said music data sequence comprising~~including at least a first and a second message type, the first type messages note events and light configuration messages, the note events~~ containing information for notes to be played, and the second type light configuration messages mapping locations of lights to be activated to the notes in the note events and containing other music related information for the mobile communication terminal,

a loudspeaker connected to a sound generator configured for generating audio waveforms in accordance with the information in the ~~first type~~note events messages,

a plurality of lights that can be activated by the processor unit, and

the processor unit being configured by the information in ~~second type~~light configuration messages to activate the lights based on the information contained in the ~~first type messages~~note events of the music data sequence, wherein the ~~second type~~light configuration messages contain data mapping ~~the~~a simultaneous activation of the lights to the note information in the note events ~~in the first type note events message~~ and the mapping reduces the number of available notes to the number of available light locations.

2. (Cancelled)

3. (Currently Amended) A mobile communication terminal according to claim 21, wherein the ~~first-type messages~~note events comprise note-on events and note-off events, and said processor unit is configured to use a last event in the ~~first type messages~~note events when one light or one light group is mapped to one or more notes at the same time.

4. (Currently Amended) A mobile communication terminal according to claim 1, in which the lights are distributed over a plurality of different locations of the terminal, and the ~~second-type~~light configuration messages contain data mapping the location of the lights to be simultaneously activated to the notes in the ~~first-type message~~note events, and the processor unit being configured to activate lights at locations in accordance with the information in the ~~second-type~~light configuration messages.

5. (Currently Amended) A mobile communication terminal according to claim 1, comprising lights in a plurality of different colors, the ~~second-type~~light configuration messages containing data mapping the color of the lights to be activated to the notes in the ~~first-type~~note events message and the processor unit being configured to activate lights with the color in accordance with the data in the ~~second-type~~light configuration messages.

6. (Currently Amended) A mobile communication terminal according to claim 1, wherein the ~~second-type~~light configuration messages contain data mapping the intensity or intensity profile of the lights to be activated to the information in the ~~first type~~note events message, and the processor unit being configured to activate lights

with the intensity in accordance with the mapping data in the ~~second-type~~light configuration messages.

7. (Currently Amended) A mobile communication terminal according to claim 6, wherein the ~~first-type~~note events messages contains the velocity of the notes, and the intensity of the light to be activated is mapped to the velocity of the notes concerned.

8. (Currently Amended) A mobile communication terminal according to claim 1, wherein ~~and the second-type~~light configuration messages contain data mapping the location of the lights to be activated to the notes in the ~~first-type~~note events message, and the processor unit being configured to activate lights at locations in accordance with the information in the ~~second-type~~light configuration messages.

9. (Currently Amended) A mobile communication terminal according to claim 1, wherein the ~~second-type~~light configuration message contains data mapping the activation of groups of lights to be activated simultaneously to the note information in the ~~first-type~~note events messages, and the processor unit being configured to activate the groups of lights in accordance with the data in the ~~second-type~~light configuration messages.

10. (Original) A mobile communication terminal according to claim 9, wherein a group of lights to be activated comprises a plurality of lights arranged in a recognizable pattern.

11. (Currently Amended) A mobile communication terminal according to claim 1, wherein said music data is arranged in a number of channels and the ~~first-type~~note events messages are assigned to one of the channels, and ~~first-type~~note events messages used for activating the lights are assigned to a specific one of the channels.

12. (Original) A mobile communication terminal according to claim 11, wherein the volume setting for the channel used for activating the lights is set to zero to create a dedicated light activation channel.

13. (Previously Presented) A mobile communication terminal according to claim 1, wherein the mapping comprises a function whose arguments comprise the note number.

14. (Previously Presented) A mobile communication terminal according to claim 13, wherein a first parameter is added or subtracted from the note number and the result is integer or modulo divided by a second parameter in the function.

15. (Cancelled).

16. (Previously Presented) A mobile communication terminal according to claim 13, wherein the function reduces the number of available notes to the number of available light colors.

17. (Previously Presented) A mobile communication terminal according to claim 13, wherein the mapping comprises a random function.

18. (Previously Presented) A mobile communication terminal according to claim 1, wherein the mapping comprises a look up table.

19. (Currently Amended) A mobile terminal according to claim 18, wherein the terminal comprises a vibrator, a flashlight or a camera flash and the processor being configured by ~~second type~~light configuration message to activate the vibrator flashlight or camera flash based on the information contained in the ~~first type~~note events messages.

20. (Currently Amended) A mobile communication terminal according to claim 1, further comprising an editor application enabling a user to create or edit the ~~second type~~light configuration messages.

21. (Previously Presented) A mobile communication terminal according claim 20, wherein the editor application enables the user to select the channel to be used, to select the patterns to be activated, or to modify the function.

22. (Previously Presented) A mobile communication terminal according claim 20, wherein the terminal comprises different ranges of lights, and the editor application enables the user to select the range.

23. (Previously Presented) A mobile communication terminal according claim 20, wherein the editor application enables the user to map the intensity to the velocity, to a given fixed parameter, or to a random number.

24. (Currently Amended) A mobile terminal according to claim 20, wherein the editor application enables the user to edit the music data contained in the ~~first type~~note events messages to add, delete or change notes and note related information.

25. (Previously Presented) A mobile terminal according to claim 1, wherein the music data is a MIDI sequence or file.

26. (Currently Amended) A mobile terminal according to claim 25, wherein the ~~second type~~light configuration messages are System Exclusive Message and the ~~first type~~note events messages are channel voice messages, NOTE ON and NOTE OFF messages.

27. (Currently Amended) A method for controlling the activation of lights of a mobile communication terminal configured to play music from music data including at least a ~~note events message~~first and a ~~second~~light configuration message ~~type~~, the ~~first message type~~note events message containing information for notes to be played ~~and~~, the ~~second message type~~light configuration message mapping locations of lights to be activated to the notes in the note events message and containing other information for the device that is to reproduce the music, ~~and comprising placing in the second type messages data mapping the activation of the lights based on the information contained in the~~ ~~to the note information~~events of the music data contained in the first type messages, and wherein the ~~second type~~light configuration messages contain data mapping ~~the~~ a simultaneous activation of the lights to the notes information in the ~~first type~~note events message and the mapping reduces the number of available notes to the number of available light locations.

28. (Currently Amended) A method according to claim 27, wherein data mapping the position of lights to be activated is placed in the ~~second-type~~light configuration messages.

29. (Currently Amended) A method according to claim 27, wherein data mapping the color of lights to be activated is placed in the ~~second-type~~light configuration messages.

30. (Currently Amended) A method according to claim 27, wherein data mapping the intensity of lights to be activated is placed in the ~~second-type~~light configuration messages.

31. (Currently Amended) A method according to claim 27, wherein data mapping the simultaneous activation of groups of lights arranged in recognizable patterns to be activated, is placed in the ~~second-type~~light configuration messages.

32. (Currently Amended) A method according to claim 27, wherein a function whose arguments include the note number is placed in the ~~second-type~~light configuration messages.

33. (Previously Presented) A method according to claim 32, further comprising adding or subtracting a first parameter from the note number and integer or modulo dividing the result by a second parameter.

34. (Cancelled)

35. (Previously Presented) A method according to claim 32, wherein the function reduces the number of available notes to the number of available light colors.

36. (Previously Presented) A method according to claim 32, further comprising the step of applying a random function in the mapping.

37. (Previously Presented) A method according to claim 27, further comprising the step of using a look up table for the mapping.

38. (Previously Presented) A method according to claim 27, wherein the music data is a MIDI sequence or file.

39. (Currently Amended) A method according to claim 38, wherein the ~~second~~ light configuration messages are System Exclusive Messages.

40. (Currently Amended) A method according to claim 27, wherein one of more ~~second~~ light configuration messages are placed in the beginning of the music data file or sequence for initializing the mapping.

41. (Currently Amended) A method according to claim 40, in which further ~~second~~ light configuration messages are placed later in the music data file or sequence for changing the mapping, the ~~second~~ light configuration messages all being located within one track.

42. (Currently Amended) A computer terminal comprising:

a processor unit controlling the terminal,

a user interface comprising a keyboard and a display,

an electronic memory having music data stored thereon, said music data including at least a ~~first~~ note events message and a ~~second~~ light configuration message ~~type~~, the ~~first~~ note events messages containing information for notes to be played, the ~~second~~ light configuration messages ~~containing information for mapping locations of lights to be activated~~ the activation of lights on a mobile communication terminal to the note information in the ~~first~~ note events messages, and wherein the ~~second~~ light configuration messages contain data mapping the activation of the lights to the notes in the ~~first~~ note events message, the light configuration messages contain data mapping a simultaneous activation of the lights to the note information in the note events message and the mapping reduces the number of available notes to the number of available light locations,

a loudspeaker connected via an amplifier to a sound generator capable of generating audio waveforms in accordance with the music data, and

an application for creating and/or modifying the ~~second~~ light configuration messages.

43. (Original) A computer terminal according to claim 42, wherein the application is configured to emulate the activation of the lights of a mobile terminal on the display of the computer terminal.

44. (Original) A computer terminal according to claim 42, wherein the application is configured for controlling lights of a mobile communication terminal connected thereto for allowing the testing of the activation of the lights directly on the mobile communication terminal.

45. (Currently Amended) A music data sequence or file for use on a mobile communication terminal, said music data file containing at least:

~~first-type~~note events messages with note information, and

~~second-type~~light configuration messages mapping ~~the~~a simultaneous activation of lights of a mobile communication terminal to the note information contained in the ~~first-type~~note events messages, wherein the ~~second-type~~light configuration messages contain data mapping a location and the activation of the lights to the note information in the ~~first-type~~note events message and the mapping reduces a number of available notes to a number of available light locations.

46. (Currently Amended) A music data sequence or file according to claim 45, wherein the ~~first-type~~note events messages contain information mapping the activation of lights to the note-on commands, and information mapping the deactivation of lights to note-off commands.

47. (Currently Amended) A music data sequence or file according to claim 45, wherein the ~~first-type~~note events messages contain velocity information associated with a note-on command, and the ~~second-type~~light configuration messages contain information mapping the intensity of a light to be activated to the velocity information.

48. (Currently Amended) A music data sequence or file according to claim 45, wherein the ~~first-type~~note events messages contain the note number associated with a note-on or note-off command, and the ~~second-type~~light configuration messages contain a function whose arguments comprise the note number.

49. (Original) A music data sequence or file according to claim 48, wherein the function reduces the range of note numbers to the range of light locations on the mobile communication terminal.

50. (Original) A music data sequence or file according to claim 49, wherein the function reduces the range of note numbers to the range of light colors on the mobile communication terminal.

51. (Previously Presented) A music data sequence or file according to claim 45, wherein the music data or sequence is in a MIDI format.

52. (Currently Amended) A music data sequence or file according to claim 51, wherein the ~~second-type~~light configuration messages are system exclusive messages.

53. (Previously Presented) A music data sequence or file according to claim 45 stored in a computer medium.

54. (New) The mobile communications terminal according to claim 1 wherein the note events are passed to an audio portion of the processor and a light controller, and the light configuration message is passed to a light configuration database, the light

controller being configured to search the light configuration database for configuration information corresponding to the note events when the note events are detected.